

PRAMAC P 6000s

Item code: PF532MYA001



(purely indicative picture)

Main features

Power (LTP): 5.87 kW
Voltage: 120, 240 V
Frequency: 60 Hz
Engine manufacturer: Yanmar
Fuel type: Diesel
Starting system: Recoil,
Electric

P Series Diesel

The P Series is exceptionally quiet and designed for residential areas or worksites where low noise level is required or desired.

Technical specifications

Single Phase	
Power (LTP)	5,87 kW
Power (COP)	4,81 kW
Power specifications	
Voltage	120, 240 V
Amps at 120V (LTP)	48,9 A
Amps at 120V (COP)	40,1 A
Amps at 240V (LTP)	24,5 A
Amps at 240V (COP)	20 A
Frequency	60 Hz
Power factor	1 cosPhi
Engine specifications	
Engine manufacturer	Yanmar
Model	L100
Fuel type	Diesel
Displacement	406 cc
Cycle	4
Power	7,4 kW
	10 HP
Aspiration	Natural
Cooling system	Air
Starting system	Recoil, Electric

Consumption	
Fuel consumption at 75% of load	0,37 gal/h
Fuel tank capacity	5,55 gal
Running time at 75% of load	14,9 h
Noise Emission	
Noise pressure level at 7 m	65 dBA
Dimensions and weight	
Length	38,19 in
Width	22,83 in
Height	35,04 in
Weight (dry)	436,51 lb
Receptacles	
NEMA 5-20R, 125V GFCI	2
NEMA L14-30R, 125-250V TL	1
Features	
Voltage selector	No
Low oil protection	Yes
Circuit breaker	Yes
Idle-control	No
Voltmeter	Yes
Hourmeter	No
Fuel level meter	Yes
Wheel kit	Optional
Lifting kit	Yes
Mobility kit (includes lifting eye)	No
Quick connect fuel tank	No
CSA certified	No

Technical specifications are subject to change without notice. Consult your local PRAMAC representative for more information.