



SPECIFICATION SHEET

GC2-R-B4830 BATTERY SYSTEM

Battery system: GC2-R-B4830



Capacity: 30Ah

Built-in Smart Battery Management System (BMS)

ELECTRICAL SPECIFICATIONS

Voltage:	51.2V Nominal
Chemistry:	LiFePO4
Max Charge Voltage:	57.6V
Operating Voltage Range:	40.0 - 57.6V
Ah Capacity:	30Ah
Cell configuration:	16S
Max Continuous Discharge Amps:	60A
Max Discharge Peak Current Amps:	100A (10 Seconds)
Max Charge Current Amps:	30A
Charge Temp Range:	0°C (32°F) / 55°C (131°F)
Discharge Temp Range:	0°C (32°F) / 55°C (131°F)
Storage Temp:	0°C (32°F) / 30°C (86°F) (<6 Months)
Weight:	33 (LBS)
Depth Inches:	7.1
Width Inches:	10.2
Height Inches:	10.7
Safety Features:	BMS (Battery Management System) Over Voltage, Under Voltage, Over-Current, Short Circuit, Over Temperature, Under Temperature
Series I Parallel:	Max (10) in Parallel = 300 Amp Hours

DIMENSIONS



- ✓ TROJAN T-105 EXACT REPLACEMENT
- ✓ MODULE DESIGN, GC2 SIZE
- ✓ IP67 - WATERPROOF
- ✓ STACK FOR INCREASED POWER OUTPUT
- ✓ CONNECT UP TO 10 IN PARALLEL (300AH)
- ✓ 48V GOLF CARTS

INSTALLATION GUIDE

