

AIR COOLED DIESEL GENERATORS





DIMENSIONS Unit:mm (in.)

YDG-2700N W Н 500(19.69) (Recoil) 590(23.23) 416(16.38) YDG-2700N (Electric) 649(25.55) 416(16.38) 500(19.69)



ACCESSORIES

Model		YDG2700N	YDG3700N	YDG5500N	YDG6600TN				
AC dual voltage		•	• •		-				
AC breaker		0	0 0 C		0				
12V DC output		0	0	0	-				
DC breaker		0	0	0	-				
Voltage meter	Single	0	0	0	•				
	Dual	•	•	•	0				
Pilot lamp		-	-	-	-				
Oil alert		0	0	0	0				
Fuel gauge		0	0	0	0				
Recoil start		0	0	0	-				
Electric start		•			0				
Tool set		0	0	0	0				

YANMAR CO.,LTD.

1-32, Chayamachi, Kita-ku, Osaka 530-8311, Japan Telephone:+81-6-6376-6411 Facsimile:+81-6-6377-1243 www.yanmar.co.jp

YDG-3700N





Control panel: YDG3700N-E

Note : All data subject to alteration without notice.

The New YDG from Yanmar For Power and Economy

If you are looking for a silent, compact, power source, with minimum fluctuations, the YDG is waiting for you. Durability and long operation are designed in. Mobility approaches that of a gasoline generator. And the direct injection air-cooled diesels, the amongst smallest in the world, offer very good fuel savings. The power is high. The cost is low. Specifications and accessories are available for most markets. Listen carefully, or you might not even notice they're at work.

Versatile power

An AVR (Automatic Voltage Regulator) gives lowfluctuation power delivery at a selection of voltages form 110V to 240V. Each model also makes available12V D.C - really useful for charging car/boat batteries.(excluding 3-phase models)

Dusk-to-dawn Operation without Fill-up

A single tankful of diesel will keep these aircooled gensets on the go for 6~9.5 hours. The secret to such long operation is their low fuel consumption from features like direct injection- a major feat for this type of compact engine. These gensets give savings with every tankful of diesel. And they have a utility-size fuel tank, so you can leave them running all night.

Total Carry-around Convenience

The extra-lightweight YDG is as easy to move around as most gasoline units. And it's easy to store too.We've achieved it by linking together our small air-cooled diesel (the Yanmar L-N type) with a highly compact and light U-frame generator. The size and weight trimming allows you to take these ,open-type,sets anywhere.

Peaceful power; the YDG

Engine and generator rest on inclined rubber blocks. This improved mounting system takes away both vertical and horizontal vibrations, leaving you with a smoothly purring engine. Noise prevention measures are taken at several levels; at intake, in the combustion system and through the well muffled exhaust system.

Alarm system

The chance of damage due to low oil level operation is reduced with a Yanmar genset. An alarm is activated and the engine stops as soon as the oil falls low. Besides, the sockets on the control panel are recessed and the muffler is enclosed with a cover.

Instant, No-effort Starts

With a short 70cm stroke of a recoil starter, the engine jumps into life. Auto-return decompression makes starting easier and guick even when the temperature is low.



SPECIFICATIONS

Model		YDG2700N		YDG3700N		YDG5500N		YDG6600TN		
Туре		Revolving field type 2 pole generator								
Frequency Hz		50	60	50	60	50	60	50	60	
Max. AC outp	ut kVA	2.2	2.7	3.2	3.7	4.6	5.5	5.5	6.6	
Cont. AC outp	out kVA	2.0	2.5	3.0	3.5	4.2	5.0	5.0 (1.7)	6.0 (2.0)	
ថ DC output(gei	nerator&charger) V-A			12-	12-8.3				-	
B Voltage	V			120, 220, 240, 110 / 220, 120 / 240				380 (220)		
Rated power	actor %	100						80 (100)		
Phase		Single phase						3-phase(single)		
Excitation sys	tem	Self-excitation					Self & separate excitation			
Model		L48N5/	6-G(E)Y	L70N5/6-G(E)Y		L100N5/6-G(E)Y		L-100N5/6-GEYT		
Туре		Vertical, 4-cycle, air-cooled diesel engine								
Displacement	Displacement cc		219		320		43		35	
Cont. output	kW/min ⁻¹ (rpm)	2.8/3000	3.1/3600	4.1/3000	4.4/3600	5.7/3000	6.6/3600	5.7/3000	6.6/3600	
Starting syste	em			Recoil or Recoil / Electric			Electric			
Combustion s	ystem	Direct injection								
Governor sys	em	All speed by centrifugal weight								
Fuel oil		Diesel fuel oil								
Fuel tank capa	acity lit.	7	.2	13						
Lube oil capad	city lit.	0.8		1.1			1.65			
Operation cap (One tankful)*		7.0	6.5	9.5	8.0	7.0	6.0	5.5	4.9	
Noise level at	7m (approx.) dB (A)	79	80	81	82	84	85	84	85	
Dimensions L>	(WxH(Recoil) mm	590 x 416 x 500		650 x 496 x 530		720 x 480 x 578		-		
Dry weight (Re	ecoil) kg	55		70		95		-		
	(WxH(Electric) mm	649 x 416 x 500		650 x 496 x 530		720 x 480 x 578				
Dry weight (El	ectric) kg	64		82			108			

Easy Maintenance, Long lasting

Fewer parts mean fewer maintenance worries inspection is easy and adjustments simple. Forced lubrication feeds oil to vital parts, and high quality materials give first-class durability.

AIR-COOLED DIESEL ENGINE L-N SERIES

Its secret is Yanmar's micro-size fuel injection system.

The fuel injection system the heart of a diesel. has been refined through years of research and development at Yanmar. We have now succeeded in minimizing the weight



and size of this equipment and simplifying the structure by adoption of a bushless pump and a smaller nozzle.



- Durable because it is built by a specialist in large diesel technology.
- Convenient Recoil startera feature commonly associated with gasoline engines.
- Fuel costs dip to a new low with Yanmar's direct fuel injection system.
- Very low vibration and quiet running make it ideal, a popular choice for constantly operating machinery.